

CALA 110H

CALA 140H

CALA 160H



EUROTRON



Temperature and speed settings

### Mounting, hot and cold laminator

Improved version of CALA110 wide cold laminator for laminating, mounting, application tape and adhesive fixing equipped with a user friendly digital control panel for managing speed and temperature of the upper heated roller (up to 60° C) in order to get a perfect result depending on the support to be processed or the laminating material to be used.

Additional lower shaft to be used as double-sided tape holder in order to laminate and apply adhesive tape at the same time.



	CALA 110H	CALA 140H	CALA 160H
Working width (mm)	1080	1400	1600
Paper input width (mm)	1120	1420	1620
Upper roller temperature (°C)	60	60	60
Lower shaft for double-side adhesive tape included	•	•	•
Manual rollers opening for panel mounting (mm)	up to 20	up to 20	up to 30
Speed (m/min)	up to 3	up to 3	up to 3
Additional shaft with roll support	•	•	•
Electric pedal control	•	•	•
Power requirements (V - Hz)	230 - 50/60	230 - 50/60	230 - 50/60
Power consumption (kW)	1,25	1,7	2,7
Dimensions (mm)	1400x1200x600	1750x1200x600	2000x1250x700
Weight (kg)	150	180	280

**Huvudkontor**  
Eurotron Graphics KB  
Lindenro  
295 72 Gualöv

**Besöksadress**  
Storgatan 79  
362 30 Tingsryd

**Lager**  
Östra Vittusgatan 36  
371 33 Karlskrona

**Telefon**  
+46 (0)46 18 46 00  
**Hemsida**  
www.eurotron.se

**E-post**  
marknad@eurotron.se