



▼ SKY LAM 380 Super



◀ SKYLAM Foliering

▼ Chrome Top Heating Roller



▼ Anti Curl Control System




▼ Slitter



▼ Perforator



▼ Infrared Sensor



◀ Dual LCD
(*option)



◀ Special Core Unit
3 sizes
(25, 58 and 76 mm)
in one unit



◀ Max. Laminating
Roll Film

[www.skydsb.com/download/sky lam 380 super dual.avi](http://www.skydsb.com/download/sky%20lam%20380%20super%20dual.avi)

- End cutter, air cooling fan, emergency stop switch and safety guard are installed basically.
(*Option : Stand for 380 Super)
- Auto Power Off and Memory function.

MODEL	SKY LAM 380 Super	SKY LAM 380 Super Foliering
Max. Laminating Width	350 mm (13.8")	350 mm (13.8")
Max. Laminating Speed	6 m/min	5 m/min
Max. Laminating Thickness	13 mm	
Heating System	Heating roller internal heater	
Q'ty of Roller	4	
Temperature Control	Yes	
Speed Control	Yes	
Display	LCD	
Preheating Time	8 min.	
Power Supply	AC 100, 110, 120, 230, 240V (50/60Hz)	
Power Consumption	1,550 watts	
Dimension	700 x 460 x 272 mm	700 x 460 x 272 mm
Weight	55 kgs	55 kgs
Operation Temperature	0 - 150°C	

MICOM SYSTEM

Huvudkontor
Sigraphics KB
Storgatan 79
362 30 Tingsryd

Besöksadress
Storgatan 79
362 30 Tingsryd

Lager
Östra Vittusgatan 36
371 33 Karlskrona

Telefon
+46 (0) 46 18 46 00
Hemsida
www.sigraphics.se

E-post
marknad@sigraphics.se