



Astrojet L1 color label printer



Astrojet L1 color label printer

This printer is the newest generation of our successful printer, the AstroJet M1-C color label printer. The specifications of both printers are mainly the same:

- Print speed up to 18m / min.
- High print quality of 1600x1600dpi
- Exceptionally low printing costs
- Little or no maintenance required



Next to this, the AstroJet L1 now offers even more possibilities:

Thanks to the new technology and its moveable printhead, it is possible to interrupt the printing and restart it without the need to cut the paper path. This makes it possible to:

- Printing larger roll-to-roll jobs
- Link the printer to a labeling unit for "print and apply" applications
- Positioning the printer in-line with balance solutions
- Linking the printer to a (semi-rotative) die-cutting machine
- ...

In short, this printer has more possibilities that allow you to make an investment within the needs of your company.

Standard options:

- Unwinder and rewinder
- F1 Semi rotary finisher for larger productions

Astrojet L1 inkjet kleurenprinter

Preliminary specifications

| | |
|-------------------------|--|
| Print Resolution | Best: 1600 x 1600 DPI Normal: 1600 x 800 DPI |
| Print Speed | Best quality: 15 cm/sec. Normal quality: 30 cm/sec. |
| Speed un- and rewinder | 0-125 RPM |
| Print sizes | 220,8mm B x continuous length |
| Media types | Roll-to-roll or fanfold |
| Media Sizes | Minimum: 50,8m x 57mm Maximum: 228,6 mm B x continuous length |
| Paper Thickness | Minimum: 0,1 mm Maximum: 0,3 mm |
| Min. label Gap | No bleed: 3mm Full bleed: 5 mm |
| Roll Dimensions | Minimum: 50,8 mm x 254 mm Maximum: 228,6 mm x 254 mm Core: 76 mm |
| Media sensor | continuous, blackmark, diecut |
| Software | Windows Printer Drivers for Windows, 8; 8.1; 10 RIP available |
| Ink | cartridges of 250 ml Water-based inkjet CMYKK |
| Printhead | interchangeable Memjet printhead |
| Connection | USB 2.0 and Ethernet connection |
| Electricity | 115-240 VAC, 50/60 Hz |
| Internal Memory Battery | CR 2032 Lithium battery |
| Dimensions | 51,4 cm x 56,5 cm x 34,3 cm |
| Weight | 34 kg |

Huvudkontor
Sigrotor Graphics KB
Storgatan 79
362 30 Tingsryd

Besöksadress
Storgatan 79
362 30 Tingsryd

Lager
Östra Vittusgatan 36
371 33 Karlskrona

Telefon
+46 (0) 46 18 46 00
Hemsida
www.sigraphics.se

E-post
marknad@sigraphics.se